

Natures Secret Weapon
Anti Seize | Assembly Lubricant | Rubber Grease



- FEATURES:**
- Non Perishing to rubber
 - Stops galling & binding
 - Di-electric properties to 70kV
 - Food Grade
 - Low Toxicity
 - Low Eco-Toxicity
 - Classified as Non-Hazardous
 - Derived from natural, sustainable ingredients
 - Acid & Salt resistant

Size	Part No.	Size	Part No.
235ml	GS\0235	1 Litre	GS\0001
250ml Tube	GS\250T	4 Litre	GS\0004
500ml	GS\0500	20 Litre	GS\0020
500ml Cartridge	GS\C500	200 Litre	GS\0200

CONTENTS: Pure industrial grade lanolin

APPLICATIONS:

- Anti-seize for nuts, bolts, shackles and threaded rod
- Assembly lubricant & rubber grease
- Protection of electrical equipment and components from moisture ingress, including multi-pin plugs & connectors
- Prevents galling of stainless steel and aluminium
- Stops electrolysis due to similar metals
- Wire rope lubrication and corrosion protection (via injection)
- Lubricant for rubber hoses, linkages, pivot pins & bushes
- Belt dressing
- Soft seal gasket
- Drilling & cutting aid
- Welding nozzle dip
- Timber end grain protection

PHYSICAL PROPERTIES:

- **Appearance:** Light brown coloured solid
- **Boiling Point/Range (°C):** >250
- **Flash Point (°C):** >200
- **Specific Gravity (g/100g @ 20°C):** 0.92
- **Demulsibility (mins):** Immiscible

STORAGE & TRANSPORT:

- All sizes are classified as Non Dangerous Goods
- Keep in cool, dry, well ventilated place
- Keep out of reach of children
- Shelf life - 7 years if kept sealed in reasonable conditions

For safe handling of this product, please consult the Safety Data Sheet (SDS)

Always read entire label before using product

PREPARATION:

- Lanotec Type A Grease will give best results when applied to a clean, dry surface.

APPLICATION:

- Smear onto thread and underside of bolt head. Wipe off excess before tensioning.
- Fill one half of electrical plug to create moisture / dust proof barrier before reconnecting electrical connector.
- Smear grease between dissimilar metals before tightening.
- Smear one flange face only for use as a soft seal gasket.
- Smear O-ring or seal with Type A Grease to hold in place during assembly.
- For wire rope: wipe onto wire rope by hand whilst undertaking regular inspection, or use pressurised applicator such as Masto, Viper, or Raptor.
- Apply directly to squealing belt as a belt dressing (softens and moisturises belt).
- Apply via pump or hand to all shafts and pins prone to drying out or seizing.
- Dip fastenings into product for reduced friction on drills etc and provide internal protection when fixed into timber.

REMOVAL:

- If removal of Lanotec Type A Grease is required, Lanotec Citra-Force or Lanotec PowaWash is recommended

APPROVALS:

- HACCP Australia Food Safety Accreditation Systems - Food Grade Lubricant
- AQIS Acceptance of Chemical Compound for use in Export Meat Establishments - Category 10 Lubricant Type A
- NZFSA Approval Lubricant C12
- Halal Certification Authority Australia - Taher Accreditation

TESTING:

- Torque Coefficient (K Factor) - MTS Metallurgical Testing Services - The Torque Coefficient (K Factor) of the lubricant was determined to be 0.15

Approvals and Testing documents can be provided on request

LEGAL NOTE:

The information, and the recommendations relating to the application and end use of Lanotec products, are given in good faith based on Lanotec's current knowledge and experience of the products when properly stored, handled and applied under normal conditions, in accordance with Lanotec's recommendations. However due to differences in materials, site conditions or any other factor that could affect performance, Lanotec makes no other warranty, either express or implied, concerning this product. There is no warranty in respect of merchantability. Nor can one be inferred either from this information, or from any written recommendations, or from any other advice offered. Lanotec makes no warranty in regards to the performance of the product, once applied by the user. The purchaser / user assumes all risks associated with application of the product.

The user of the product must test the product's suitability for the intended application and purpose. Lanotec reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request, and can be found on the Lanotec website.

FOR MORE INFORMATION:

Lanotec Australia Pty Ltd
PO Box 360 Archerfield QLD 4108
07 3373 3700
info@lanotec.com.au

For safe handling of this product, please consult the Safety Data Sheet (SDS)